



<b>Product Code</b>	OHS-CHR-1619
<b>Description</b>	Single Function 200X200mm Square Shape Maze Overhead Shower, Stainless Steel
<b>Flow Rate</b>	42.16 LPM @ 3 bar
<b>Flow regulator</b>	By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM, & GC-12.0 LPM @ 3.0 Bar pressure) one can regulate the flow rate.
<b>Recommended Water Pressure</b>	0.5 Bar - 3.0 Bar
<b>Mount Type</b>	Wall Mounting
<b>Spray Modes</b>	Single Function
<b>Material Composition Specification in Percentage</b>	<p><b>“Brass Rod as per IS:319-1989</b> Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p><b>STAINLESS STEEL:</b> Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304)</p> <p><b>ABS:</b> Specific Gravity (g/cm<sup>2</sup>) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (OC) 78-102”</p>
<b>Technology</b>	<b>Advanced Rubit</b> - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.
<b>Registered design no.</b>	276017
<b>Finish</b>	“Salt Spray (350 hrs + Validated) Adhesion (Pass)”
<b>Available Finishing</b>	Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Black Matt (BLM), Gold Dust (GDS), Full Gold (GLD), Graphite (GRF), Stainless Steel Finish (SSF) & White Matt (WHM)
<p>DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.</p>	