





OHS-CHR-1633
Single Function 300mm dia Round Shape Maze Overhead Shower, Stainless Steel
42.00 LPM @ 3 bar
By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM, & GC-12.0 LPM @ 3.0 Bar pressure) one can regulate the flow rate.
0.5 Bar - 3.0 Bar
Wall Mounting
Single Function
Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder) STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) ABS: Specific Gravity (g/cm2) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (0C) 78-102
Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.
276016
Salt Spray (350 hrs + Validated) Adhesion (Pass)
Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Black Matt (BLM), Gold Dust (GDS), Full Gold (GLD), Graphite (GRF), Stainless Steel Finish (SSF) & White Matt (WHM)

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.